



**Read**

(1) Sl. No	(2) Technical Specification	(3) Whether the item proposed to be supplied has specifications as given in Column (2). Write Yes or No.
1.	<p><b><u>3G-SDI Optical to Electrical Converter</u></b>  <b><u>Specifications</u></b>                      General Power 5 VDC 3.5W max                      Control and Monitoring DIP configuration, SNMP and Web interface monitoring                      Temperature range 0 to +40°C                      Supported standards SMPTE292M, SMPTE259M, SMTE297MSMPTE305.2M, SMPTE310M, SMPTE424M, DVB-ASI EN50083-9                      Optical sensitivity -30dBm or better                      Optical window 1200-1620nm</p>	
2.	<p><b><u>3G-SDI Electrical to Optical Converter</u></b>  <b><u>Specification</u></b>                      General Power 3.5W/5V                      User interface Status LED, Status GPI, configuration DIP switches and Web interface monitoring                      Temperature range 0 to +40°C                      Supported standards SMPTE 259M, SMPTE 292, SMPTE 424M, SMPTE 310M, SMPTE 297 EN50083-9</p>	
3.	<p><b><u>Frame Enclosure for Cards</u></b>  <b><u>Specifications</u></b>                      Dimension Standard Rack Mounting not More than 3 RU                      Dual Power Supply 220v@50Hz                      Compatibility Must be compatible with all the quoted cards</p>	

(ii) **Item Description at Sr. Nos. 1, 2 and 3 of Annexure-IV (Financial Bid Document) may be read as under:**

**For**

(1) Sl. No.	(2) Item Description	(3) Rate in Rs. (per Unit) (excluding GST)	(4) Qty	(5) Total Amount In Rs. (Col.3) x(Col. 4)
1.	<p><b><u>3G-SDI Optical to Electrical Converter with required cable and Accessories</u></b>  <b><u>Specification</u></b>                      General Power 5 VDC 3.5W max                      Control and Monitoring DIP configuration, SNMP and Web interface monitoring                      Temperature range 0 to +40°C                      Supported standards SMPTE292M, SMPTE259M, SMTE297MSMPTE305.2M, SMPTE310M, SMPTE424M, DVB-ASI EN50083-9                      Optical sensitivity -30dBm or better                      Optical window 1200-1620nm                      Automatic Change Over YES</p>		07	

(1) Sl. No.	(2) Item Description	(3) Rate in Rs. (per Unit) (excluding GST)	(4) Qty	(5) Total Amount In Rs. (Col.3) x(Col. 4)
2.	<p><b><u>3G-SDI Electrical to Optical Converter with required cable and accessories</u></b></p> <p><b><u>Specifications</u></b>            General Power 3.5W/5V            User interface Status LED, Status GPI, configuration DIP switches and Web interface monitoring            Temperature range 0 to +40°C            Supported standards SMPTE 259M, SMPTE 292, SMPTE 424M, SMPTE 310M, SMPTE 297 EN50083-9</p>		07	
3.	<p><b><u>Frame Enclosure For Cards with required cable and accessories</u></b></p> <p><b><u>Specifications</u></b>            Dimension Standard Rack Mounting not More than 3 RU            Power Supply 220v@50Hz            Compatibility Must be compatible with all the quoted cards</p>		04	

**Read**

(1) Sl. No.	(2) Item Description	(3) Rate in Rs. (per Unit) (excluding GST)	(4) Qty	(5) Total Amount In Rs. (Col.3) x(Col. 4)
1.	<p><b><u>3G-SDI Optical to Electrical Converter with required cable and Accessories</u></b></p> <p><b><u>Specification</u></b>            General Power 5 VDC 3.5W max            Control and Monitoring DIP configuration, SNMP and Web interface monitoring            Temperature range 0 to +40°C            Supported standards SMPTE292M, SMPTE259M, SMTE297M, SMPTE305.2M, SMPTE310M, SMPTE424M, DVB-ASI EN50083-9            Optical sensitivity -30dBm or better            Optical window 1200-1620nm</p>		07	
2.	<p><b><u>3G-SDI Electrical to Optical Converter with required cable and accessories</u></b></p> <p><b><u>Specifications</u></b>            General Power 3.5W/5V            User interface Status LED, Status GPI, configuration DIP switches and Web interface monitoring            Temperature range 0 to +40°C            Supported standards SMPTE 259M, SMPTE 292, SMPTE 424M, SMPTE 310M, SMPTE 297 EN50083-9</p>		07	
3.	<p><b><u>Frame Enclosure For Cards with required cable and accessories</u></b></p> <p><b><u>Specifications</u></b>            Dimension Standard Rack Mounting not More than 3 RU            Dual Power Supply 220v@50Hz            Compatibility Must be compatible with all the quoted cards</p>		04	

2. All other terms and conditions of the tender document shall remain unchanged.

3. For detailed information, kindly refer to the tender document uploaded on the following websites:

(a) Rajya Sabha website - [www.rajyasabha.nic.in](http://www.rajyasabha.nic.in)

(b) Rajya Sanha Television website - [www.rstv.nic.in](http://www.rstv.nic.in)

(c) Central Public Procurement Portal - [eprocure.gov.in](http://eprocure.gov.in)

**Joint Director  
Rajya Sabha Television**